



# ELECTRIC

HORSEPOWER

## LPH90

**Light • Power • Heat**  
General Purpose

### Performance Features

- Output: 1,200,000 Plus BTU
- Volume: 5000~ 6000 CFM
- Pressure: 28 Inches of WC or 1 PSI
- Delta T Temperature: 0° F @ inlet - 212° F @ Outlet
- Utilizes 7.0 Gallons of Fuel/Hour
- Electrical Area Classification: General Purpose
- Power Management System
- Emergency & High Temperature Shutdown
- Over Speed Shutdown, Low Oil Shutdown
- 396 Gallon Fuel Capacity
- 56 Hours of Run time
- 110% Fluid Containment
- 4 Point Stabilization System
- Forklift Pockets and Lifting Points
- Sound Attenuated 85dB@ 10ft
- Low Maintenance
- Air Quality: 100% Flameless Breathable Hot Dry Air
- Dimension: 270" L x 104" W x 143" T
- Weight: 10450 lbs. Empty, 13301lbs Full

#### Options:

- Blower 42 Inches of WC - 1.5 PSI 6500 CFM or 55 Inches of WC-2 PSI. 6000 CFM
- 600 Gallon Fuel Capacity Triple Axial Trailer Run time 100 Hours.
- Circulating Heater for Engine.
- Light Tower Pin on/off 31 Foot Tall.
- Light Tower 4 Lights, 8 Lights, 16 Lights. 24500 Lumens/light.

- ▶ Safe Flameless Heater
- ▶ General Purpose
- ▶ Highly Efficient Fuel Usage
- ▶ Produces Clean Dry Air



### APPLICATIONS

O & G • CONSTRUCTION • FACILITIES • PIPELINES • TANKS • BOILERS • EQUIPMENT • WELL HEADS • GROUND THAW • DEHUMIDIFICATION • GRAIN DRYING • CONCRETE CURING • TEMPORARY POWER

THE LPH100 IS NOW AVAILABLE FOR SALE, RENTAL, OR RENTAL PURCHASE



**ELECTRIC**  
HORSEPOWER INC.  
[www.electrichorsepower.com](http://www.electrichorsepower.com)

Phone: 587.520.1800

Email: [sales@electrichp.com](mailto:sales@electrichp.com)

[www.electrichorsepower.com](http://www.electrichorsepower.com)